


BLANKET WARMERS IFbw

according to DIN 12880:2007-05; EN 61010-1 (IEC 61010-1); EN 61010-2-010

Standard units are safety-approved and bear the test marks:



- Interior:** stainless steel, material 1.4301 (ASTM 304), with all-round deep-drawn ribs to integrate the large-area heating with ceramic-metal sheath
- Housing:** textured stainless steel 1.4016 (ASTM 430), rear zinc-plated steel 1.0037 (St37-2), intuitively operated SingleDISPLAY (TFT colour display) with touchscreen
- Door:** fully insulated stainless steel doors with 2-point locking (compression door lock) and inner glass door, from size 450 two leaves
- Connection:** mains cable with plug (German type)
- Installation:** Sizes 110 and 260: 4 adjustable appliance feet, Sizes 450 and 750: on lockable castors
- Interfaces:**



Model sizes/Description				110	260	450	750
Stainless steel interior	Volume	l		108	256	449	749
	Width	(A)	mm	560	640	1040	
	Height	(B)	mm	480	800	720	1200
	Depth (less 39 mm for fan)	(C)	mm	400	500	600	
	Max. number of grids/shelves	number		5	9	8	14
	Max. loading per grid/shelf	kg		20		30	
	Max. loading of chamber	kg		175	300		
Textured stainless steel exterior	Width	(D)	mm	745	824	1224	
	Height (sizes 450, 750 with castors)	(E)	mm	864	1183	1247	1720
	Depth (without door handle, depth of handle +56 mm)	(F)	mm	584	684	784	
Standard equipment	Standard works calibration certificate (measuring point chamber center)	°C		+37			
	Stainless steel grid, electropolished	number		2			
	Door-open-recognition			●			
Temperature	Working temperature range	°C		at least 10 above ambient temperature up to + 80			
	Setting temperature range	°C		+20 to +80			
	Setting accuracy	°C		0.1			
Further data	Electrical load at 230 V, 50/60 Hz	W		1400	1700	1800	2000
	Electrical load at 115 V, 50/60 Hz	W		900		1500	1800
Packing data	Net weight	kg		74	110	161	217
	Gross weight (packed in carton)	kg		99	161	227	288
	Width	mm		830	930	1330	
	Height	mm		1050	1380	1440	1910
	Depth	mm		800	930	1050	
Order No. Blanket warmers I = Incubator F = Forced air circulation bw = Blanket warmer				IF110bw	IF260bw	IF450bw	IF750bw

Options	110	260	450	750
Voltage 115 V, 50/60 Hz	X2			
Accessories	110	260	450	750
Stainless steel grid, electropolished	E20165	E28891	E20182	
Perforated stainless steel shelf	B00325	B29725	B00328	
Wall bracket for wall mounting	B29758	-		
Flush-fit unit (stainless steel frame covering gap between oven and wall opening), with air slots	B29734	B29738	B29740	B29742
Flush-fit unit (stainless steel frame covering gap between oven and wall opening), without air slots	B29735	B29739	B29741	B29743
Stacking set (4 pcs) for stacking of appliances of same size	B29744	-		
Subframe, adjustable in height (height 500 mm)	B29749	B29751	B29753	-
Subframe, on castors (height 560 mm)	B29750	-		
Subframe, adjustable in height, height 130 mm	B33661	B33664	-	
Accessories Software and Connectivity	110	260	450	750
USB stick with documentation software AtmoCONTROL and operation manual. When reordering please specify serial number	B33172			
Ethernet connection cable 5 m for computer interface	E06189			
USB-Ethernet adapter	E06192			